CPS 250-150 Compressor

Portable. Powerful. Tough.



Features:

- Controlled Pressure Technology, different pressure settings at only one compressor model
- 110% Spillage Free Containment Frame
- Spin on type compressor oil separator
- Redrock™ Enclosure
- Battery Cut-off switch
- 3-layer painting
- U Flex canopy design

Options:

- · Aftercooler + Water Separator + Bypass valve
- Cold Start
- SKID mount

Compressor	CPS 250-150		
Free air delivery (FAD) @ effective working pressure	cfm	238 - 214 - 189	
Normal effective working pressure	psig	100 - 125 - 150	
Maximum unloaded pressure	psig	150	
Minimum working pressure	psig	72.5	
Air compressor outlets		2 x 3/4" + 1x 1 1/2"	
Max. sound pressure level (LPA) at 7m (23ft)	dB(A)	70	
Max. ambient temperature at sea level	F (C)	113 (45)	
Min. starting temperature (without cold start aid)	F (C)	14 (-10)	
Min. starting temperature (with cold start aid) (*)	F (C)	-4 (-20)	
Compressor oil	Gal (L)	3.0 (11.4)	
Capacity fuel tank	Gal (L)	23 (87)	
Fuel consumption @ 100% load	Gal/hr (L/hr)	3.43 (12.98)	
Fuel autonomy at full load standard	hr	6.71	
Engine		Kubota	
Model		V2403-CR-T-E4B	
Number of cylinders		4	
Displacement	L	2.4	
Power output @ normal shaft speed	hp	65	
Emissions level		Tier 4 Final	
Full load rpm	rpm	2700	
Unload rpm	rpm	1800	
Trailer undercarriage dimensions			
Length x width x height	Inches	148 x 62.7 x 63.4	
Weight (wet)	lbs (kg)	2566 (1164)	
SKID dimensions (*)			
Length x width x height	Inches	117 x 71.2 x 69.1	
Weight (wet)	lbs (kg)	2423 (1099)	

(*) Optional

People.
Passion.
Performance.





Over 110 Plus Years of Experience

Since 1901 the Chicago Pneumatic name has represented highperformance tools and equipment designed for an extensive range of applications. Today, Chicago Pneumatic has a global reach, with local customer centers around the world. Chicago Pneumatic tools and air compressors are tailored to the needs of the industrial, vehicle service, and construction markets. Every day we develop and manufacture new products that are meant to meet your demands not only today, but tomorrow as well.

For more information contact your CP Partner:	

Use only authorised parts. Any damage or malfunction caused by the use of unauthorised parts is not covered by Warranty or Product Liability.

Photos and illustrations contained herein might depict products with optional and/or extra components which are not included with the standard version of the product and, therefore, are not included in a purchase of such product unless the customer specifically purchases such optional/extra components. We reserve the right to change the specifications and design of products described in this literature without notice. Not all products are available in all markets.

Your Chicago Pneumatic Regional Sales Manager

Chicago Pneumatic Power Technique 1059 Paragon Way Rock Hill, SC 29730 USA Tel: (800) 760-4049 Fax: (800) 952-7975

